

RUT955

INDUSTRIAL CELLULAR ROUTER



RUT955 360° VIEW

// RUT955 is a highly reliable industrial LTE Cat 4 router that delivers high performance and GNSS location capabilities.

// Ethernet, Digital, and Analogue I/O, RS232, RS485, GNSS (GPS), microSD, and USB interfaces allow for an incredible variety of industrial application scenarios.

// It is equipped with connectivity redundancy via Dual SIM failover.

// It comes with RutOS which is packed with advanced software features, like Modbus, SNMP, TR-069, NTRIP, MQTT, and multiple VPN services



CONNECTIVITY

4G LTE (Cat 4), 3G, 2G

DUAL SIM

With auto failover, backup WAN and other switching scenarios

MULTIPLE INTERFACES

Wireless Access Point with Hotspot functionality

WAN FAILOVER

Automatic switching to available Backup connection

RMS MANAGEMENT SYSTEM COMPATIBLE WITH RUT955

MANAGEMENT

ALFRTS

CONFIGURATION

ACCESS

FOTA



KEY FEATURES

HARDWARE

| Mobile | 4G/LTE (Cat 4), 3G, 2G |
|------------------------|-------------------------------------------------------------------------------------------|
| CPU | Mediatek MIPS 24Kc 580 MHz |
| Storage | 16 MB Flash |
| Memory | 128 MB RAM |
| Powering option | 4pin power socket, 9-30 VDC |
| SIM | 2 x External SIM holders (2FF) |
| Antenna connectors | 2 x SMA for mobile, 2 x RP-SMA for WiFi |
| Ethernet | $4 \times 10/100$ Ethernet ports: 1 x WAN (configurable as LAN), $3 \times LAN$ |
| WiFi | IEEE 802.11b/g/n, Access point (AP), Station (STA) |
| Inputs/Outputs | On 4pin socket: 1 x Digital input, 1 x Digital open collector output |
| Status LEDs | 1 x Bi-Color connection type, 5 x Signal strength, 4 x Ethernet, 1 x Power |
| Operating temperature | -40 °C to 75 °C |
| Housing | Aluminium housing with DIN rail mounting option, plastic panels with flat mounting option |
| Dimensions (W x H x D) | 110 x 50 x 100 mm |
| Weight | 287 g |
| | |

SOFTWARE

| Operating system | RutOS (OpenWrt based Linux OS) |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile features | Auto APN, Band lock, SIM switch, Operator black/white list, Data/SMS limits |
| Network | Failover (Network backup), VLAN, QoS, Load Balancing |
| Routing | Static routes, Dynamic routes (BGP, OSPFv2, RIPv1/v2, EIGRP, NHRP), Routing rules |
| VPN and tunneling | OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard |
| Monitoring and Management | WEB UI, CLI, SSH, CALL, SMS, TR-069, SNMP, JSON-RPC, MQTT, MODBUS, RMS |
| Connection monitoring | Ping Reboot, Wget reboot, Periodic Reboot, LCP and ICMP for link inspection |
| Cloud solutions | RMS, FOTA, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx |
| Hotspot | External/Internal Radius, SMS OTP, MAC authentication, Walled Garden |
| Supported Hotspot platforms | IronWiFi, HotspotSystem, Cloud4Wi, SAI + WiFi, MugiCloud, Purple.ai |
| SMS features | SMS status, SMS configuration, Send/Read SMS via HTTP POST/GET, EMAIL to SMS, SMS to Email, SMS to HTTP, SMS to SMS, scheduled SMS, SMS autoreply, SMPP |
| Services | DDNS, VRRP, Wake On Lan (WOL), WEB filter, UPNP, Traffic Logging |

FRONT VIEW

BACK VIEW

