

# RUTX12



RUTX12 360° VIEW

### **DUAL LTE CAT 6 INDUSTRIAL CELLULAR ROUTER**

This powerful dual LTE Cat 6 router is a great fit for mission-critical applications. Two cellular modems for dual simultaneous connections, seamless mobile service switching and load balancing features make this device irreplaceable in applications where losing connection is not an option.



## 4G LTE CAT 6

Cellular speeds up to 300Mbps with Carrier Aggregation

#### **DUAL SIM**

With auto failover, backup WAN and other switching scenarios

#### WI-FI & BT

Wave-2 802.11ac Dual Band WIFI and Bluetooth LE

#### GIGABIT ETH

4 x Gigabit Ethernet ports with up to 128 port/tag-based VLANs supported





# RMS NANAGEMENT SYSTEM COMPATIBLE WITH RUTX12

**MANAGEMENT** 

**ALFRTS** 

CONFIGURATION

**ACCESS** 

FOTA



# **KEY FEATURES**

#### **HARDWARE**

Mobile	2 X 4G/LTE (Cat 6), 3G
CPU	Qualcomm, 4 x ARM Cortex A7, 717 MHz
Storage	256 MB Flash
Memory	256 MB RAM
Powering option	4pin power socket, 9-50 VDC
SIM	2 x External SIM holders (2FF)
Antenna connectors	4 x SMA for mobile, 2 x RP-SMA for WiFi, 1 x RP-SMA for Bluetooth, 1 x SMA for GPS
Ethernet	5 x 10/100/1000 Ethernet ports: 1 x WAN (configurable as LAN), 4 x LAN
WiFi	IEEE 802.11b/g/n 2.4GHz, IEEE 802.11ac/n/a 5GHz, Access point (AP), Station (STA)
GNSS	GPS, GLONASS, BeiDou, Galileo, QZSS
Bluetooth	4.0 (Low energy)
Inputs/Outputs	On 4pin socket: 1 x Digital input, 1 x Digital open collector output
Other	1 x USB host
Status LEDs	$4 \times WAN$ type, $6 \times Connection$ type, $6 \times Signal$ strength, $2 \times WiFi$ , $10 \times Ethernet$ , $1 \times Power$
Operating temperature	-40 °C to 75 °C
Housing	Aluminium housing with DIN rail mounting option and grounding capability
Dimensions (W x H x D)	132 x 44.2 x 95.1 mm
Weight	540 g

#### **SOFTWARE**

Operating system	RutOS (OpenWrt based Linux OS)
Mobile features	Multiple PDN, Auto APN, Band lock, SIM switch, Operator black/white list, Data/SMS limits
Network	Failover (Network backup), VLAN, QoS, Load Balancing
Routing	Static routes, Dynamic routes (BGP, OSPFv2, RIPv1/v2, EIGRP, NHRP), Routing rules
Monitoring and Management	WEB UI, CLI, SSH, CALL, SMS, TR-069, SNMP, JSON-RPC, MQTT, MODBUS, RMS
Cloud solutions	RMS, FOTA, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx
Hotspot	External/Internal Radius, SMS OTP, MAC authentication, Walled Garden
Supported Hotspot platforms	IronWiFi, HotspotSystem, Cloud4Wi, SAI + WiFi, MugiCloud, Purple.ai

FRONT VIEW

**BACK VIEW** 

