

TRB141 INDUSTRIAL RUGGED GPIO LTE GATEWAY







Copyright © 2024, UAB TELTONIKA NETWORKS. Specifications and information given in this document are subject to change by UAB TELTONIKA NETWORKS without prior notice.



KEY FEATURES

FLYER // TRB141

HARDWARE

Mobile	4G/LTE (Cat 1), 3G, 2G
CPU	Qualcomm, ARM Cortex A7, 1.2 GHz
Storage	512 MBytes Flash (200 MBytes for userspace)
Memory	128 MBytes RAM (50 MBytes for userspace)
Powering option	4pin power socket, 9-30 VDC
SIM	1 x Internal SIM holder (2FF)
Antenna connectors	1 x SMA for mobile
Inputs/Outputs	On 4pin socket: 2 x Digital input/Digital open collector output (configurable) On 16pin socket: 1 x Isolated input, 1 x Single wire input, 1 x Analog input (with 4-20mA capability), 1 x Latching relay output, 1 x Non-latching relay output, 2 x Dry/Wet input (configurable)
Other	1 x Micro USB slave
Status LEDs	3 x Connection type, 5 x Signal strength, 1 x Power
Operating temperature	-40 °C to 75 °C
Housing	Aluminium housing with DIN rail mounting option
Dimensions (W x H x D)	74.5 x 25 x 64.4 mm
Weight	136 g

SOFTWARE

RutOS
TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSLv3, TLS 1.3, ARP, PPP, PPPoE, DHCP, Telnet
OpenVPN, IPsec, GRE, PPTP, SSTP, Stunnel, DMVPN L2TP, ZeroTier, WireGuard
WEB UI, CLI, SSH, CALL, SMS, TR-069, SNMP, JSON-RPC, MQTT, MODBUS, RMS
Ping Reboot, Wget reboot, Periodic Reboot, LCP and ICMP for link inspection
RMS, FOTA, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx
DDNS, WEB filter, Traffic Logging

