

TRB145 INDUSTRIAL RUGGED LTE RS485 GATEWAY

// TRB145 is a mission-critical LTE Cat 1 gateway, equipped with



FLYER // TRB145

TRB145 360° VIEW



RMS REMOTE MANAGEMENT SYSTEM **IBLE WITH TCR100** HUM PA MANAGEMENT **ALERTS** CONFIGURATION ACCESS FOTA

Copyright © 2024, TELTONIKA NETWORKS. Specifications and information given in this document are subject to change by TELTONIKA NETWORKS without prior notice.

TELTONIKA | Networks

KEY FEATURES

HARDWARE

Mobile	4G/LTE (Cat 1), 3G, 2G
CPU	Qualcomm, ARM Cortex A7, 1.2 GHz
Storage	512 MB, SPI Flash
Memory	128 MB, DDR2
Powering option	4-pin power socket, 9-30 VDC
SIM	1 x Internal SIM holder (2FF)
Antenna connectors	1 x SMA for mobile
Inputs/Outputs	On 4-pin socket: 2 x Digital input/Digital open collector output (configurable)
Serial	1 x RS485
Other	1 x Virtual network interface via micro USB
Status LEDs	3 x Connection type, 5 x Signal strength, 1 x Power
Operating temperature	-40° C to 75° C
Housing	Aluminium housing with DIN rail mounting option
Dimensions (W x H x D)	74.5 x 25 x 64.4 mm
Weight	130 g

SOFTWARE

Operating system	RutOS
Network protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSLv3, TLS 1.3, ARP, PPP, PPPoE, DHCP, Telnet
Monitoring and Management	WEB UI, CLI, SSH, CALL, SMS, TR-069, SNMP, JSON-RPC, MQTT, MODBUS, RMS
Connection monitoring	Ping Reboot, Wget reboot, Periodic Reboot, LCP and ICMP for link inspection
Cloud solutions	RMS, FOTA, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx
Modbus	TCP client, TCP server, RTU server, RTU gateway, Modbus over MQTT
Serial	Console, Over IP, Modem, NTRIP, Modbus

