



AU 2-PIN POWER SUPPLY/9W

PARAMETER

| PARAMETER | RATED VALUE | ABSOLUTE MAXIMUM |
|------------------------------|-------------|------------------|
| Input Voltage | 100-240 VAC | 90-264 VAC |
| Input Frequency | 50/60 Hz | 47-63 Hz |
| Input Current (@100-240VAC) | 0.4 A | - |
| Inrush Current (@100-240VAC) | - | 40 A |
| Output Voltage | 9 VDC | 8.55-9.45 VDC |
| Output Current | 0-1 A | - |
| Overshoot | 5 % | 10 % |

OTHER PARAMETERS

| | |
|-----------------------------------|--|
| Short-Circuit protection | V |
| Input protection | Fuse |
| HIPOT (Dielectric Withstand Test) | Primary to Secondary: AC3000V |
| MTBF | 50000 h |
| Input connector | AU |
| Output connector | 2-PIN, with cord end terminals |
| Certification: | IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013, AS/NZS 60950.1: 2015; AS/NZS CISPR 32: 2015; IEC 62321-7-1:2015, IEC 62321-6:2015, IEC 62321-5:2013, IEC 62321-4:2013, IEC 62321:2008 Annex C. |

